

Breader/Blender/Sifter

SPECIFICATION

The AyrKing BBSU4830 is a manual breading workstation with integrated automatic Blender/Sifter machine. AyrKing's rotary brush sifter operates without detrimental vibration or agitation. AyrKing's brush is made of spirally configured nylon bristles which form an auger to eject unwanted dough balls to waste container. During the sifting process ingredients are fully blended as the brush tumbles breading media before it exits through the sifter screen. AyrKing's unique process prevents dough ball grinding, eliminates the usual sifting noise, & blends ingredients as it ejects waste.





BBSU4830LH BBSU4830RH

ADVANTAGES

- ◆ Sift and blend 30 lbs (14 kg) of breading in 60 seconds!
- Rotary auger brush blends, sifts, and ejects dough balls simultaneously
- Blending brush action prevents ingredient segregation, unlike vibrating or agitating systems
- Quiet, vibration-free operation creates results, not disturbances
- Sixty second timed cycle frees labor and saves energy
- Raised stainless steel lip around sifter opening prevents tabletop spills from contaminating sifted breading
- Fully enclosed sifter with only four internal parts, reduces dust and allows quick and easy cleaning
- Direct drive, steel geared motor & solid stainless steel fabrication provide lasting performance

INCLUDED ACCESSORIES

B101 Red Plastic Lug Plug

B122 S/S Wire, Round Dip

Basket

B123 S/S Round Dip Pot

B302 White Plastic Breading Lug

w/Hole

B303 White Plastic Breading Lug

w/o Hole

B304 White Plastic Dough Ball

Pan

B325 White Plastic Lug Cover

OPTIONAL ACCESSORIES

B124 S/S Round Dip Pot Lid

B126 S/S Wire, Feathering Basket

B221 S/S Back Panel

B241 Swivel Casters, Four Locking

5"

B302G Gray Plastic Breading Lug w/

Hole

B303G Gray Plastic Breading Lug w/

o Hole

B325G Gray Plastic Lug Cover

B420 Bun Pan Rack, Hooks on

Back Panel (Requires B221)

MODELS


BBSU4830 48" Wide Work Area w/a


Sifter

BBSU4830LH 48" Wide Work Area w/a

Sifter, Left-Flow Configuration

| MODELS | CRATED MEASUREMENTS | | | | UNCRATED |
|------------------------|---------------------|-------------|--------------|----------------|---------------|
| | LENGTH | WIDTH | HEIGHT | WEIGHT | WEIGHT |
| BBSU4830 BBSU4830LH | 52" (1321mm) | 33" (838mm) | 44" (1118mm) | 250 lb (113kg) | 215 lb (98kg) |







ELECTRICAL

Timed control board automatically senses voltage & operates at either:

115V, 50/60Hz, 1 phase, 2.3 AMP, 184W

230V, 50/60Hz, 1 phase, 1.2 AMP, 207W

Includes universal male three prong, recessed AC receptacle

(IEC 320 C13) mating to an 10 foot (3048mm) cord with NEMA 5-15P male three prong plug



WARRANTY

One Year Parts

Ninety Days Labor

No Travel Time



2013 Cobalt Drive
Louisville, KY 40299-2417
502.266.6270 | ayrking.com







