



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- DC01 DONUT CONV KIT DF4/GAS
- CN4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm
- SLS4 Lincat Silverlink 600 Free-standing Floor Stand - for units W 450 mm

PRODUCT FEATURES

- Single tank fryer with twin basket operation giving you the flexibility to cook different foods or loads simultaneously, delivering 25kg of chips per hour
- Front mounted controls for safety
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris - gives cleaner cooking results and saves money by prolonging the life of the oil
- Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Front drain off tap for easy removal of cooking oil

Fry perfectly crisp on the outside and fluffy inside chips perfectly every single time with the Silverlink 600 Gas Single Tank Counter Top Fryer. Delivering 25kg of chips per hour, the fryer comes with two baskets which gives you the flexibility of cooking different foods or loads simultaneously. With piezo ignition for easy lighting, it's ideal for mobile operations as well as cafes, pubs and restaurants. The fryer comes with an innovative deep cool zone, which collects cooking debris to prolong the life of the oil and therefore save you money. You're in control courtesy of the accurate thermostat throughout the entire cooking process, while the flame failure device and top temperature cut out ensures a safe operation.

A/A FILE NUMBER:

ITEM NUMBER:

WEIGHTS & DIMENSIONS

| | |
|--------|---------|
| Width | 450 mil |
| Depth | 654 mil |
| Height | 415 mil |
| Weight | 30.9 kg |

SHIPPING DETAILS

| | |
|----------------------------|-------------------------|
| Ship Width | 70 cm |
| Ship Depth | 55 cm |
| Ship Height | 63.5 cm |
| Ship Weight | 33.99 kg |
| Number of Shipment Parcels | 1 |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product | No |
| Returnable Item | No |

PRODUCT CERTIFICATIONS



ENERGY SPECS

| | | | |
|----------------------------|------------------|-------------------------------------|-----------------------------|
| Primary Energy Source Type | Gas | Gas Inlet Size | 0.5 in |
| Kilowatts | 11.3 kW | Gas Inlet Pressure Required | 16.2 mBar |
| Electrical Connection Type | Direct Hardwired | Gas Total BTUs | 38555 BTU |
| Electrical Plug Type | Not Applicable | Gas Consumption at Max Use Per Hour | 1.08 m ³ |
| Number of Electrical Plugs | Not Applicable | Total Heat Input at Max Use | 11.3 kW, 38600 BTU per hour |
| Gas Type | Natural Gas | Energy Saving | No |

ADDITIONAL SPECIFICATIONS

| | | | |
|-----------------------|--|-----------------------------|------------|
| Auto Oil Top-Off | No | Number of Burners | 1 |
| Basket Lift Type | Not Applicable | Number of Vats (batteries) | 1 |
| Control Type | Mechanical | Total Oil Capacity (volume) | 8 l |
| Food Production Rate | 16kg chips - 12mm [frozen], 25kg chips - 12mm [chilled] per hour | Oil Reclamation | No |
| Fryer Type | Open Pot | Oil Temperature Control | Mechanical |
| Integrated Filtration | No | Pumped Oil Filtration | No |
| Number of Baskets | 2 | Split Pot | No |
| | | Temperature Maximum | 190 °C |
| | | Temperature Minimum | 110 °C |
| | | Vat 1 Oil Capacity (volume) | 8 l |

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

