
THE CORE 600 TECHNICAL DATA SHEET



Technical data

Model	CORE 600
Stock code	8560
Tankcapacity	25-28 litres
Dimensions [*]	600x600x850/900
Baskets*	255x285x135
Output per hour (frozen product)	57-68 kg/h
Voltage	3N400V
Heating power	22 kW
Amperage	32A per phase
Heating element	2
Temperature range	95°C – 190°C
Protection index	IPX4
Net weight	93 kg
Power cable	2.5m
Frying surface	W568xD338mm







Supplied with lid, baskets, oil bucket, crumb filter, element lifting hook and mains cable









THE CORE 600 TECHNICAL DATA SHEET



Features and benefits

- · Electromechanical thermostat with overheat protection
- · Ergonomic thermostat knob for easy temperature control
- · Integrated Sicotronic interface
- Intelligent adjustment for optimised performance and precise temperature control (+/- 6°C)
- Maximum insulation to optimise efficiency and heat retention, minimising energy loss
- Cool zone for waste collection below the heating element, slowing down oil degradation
- · Fryer can be heated for cleaning with water (95°C)
- · Rounded corners and a pivoting heating element, with an intermediate stop position, for easy cleaning
- · Folding lid for easy storage (inside fryer door)
- · MELT Position: melts solid fat without burning it
- · Easy to locate element RESET button
- High quality components and finish to meet the highest standards
- · Stainless steel, strong and durable
- · Adjustable height castors with fixed castors on rear
- Swiss Made: manufactured at the Valentine Fabrique factory in Romanel-sur-Morges
- IPX4 rating / 3-year warranty / 20-year tank warranty
- · 20-year availability of spare parts

Options

- · Built-in installation
- · Other voltages available on request

Accessories

- · Microfilter with support frame
- Fishplate
- · Batter bowl
- · Splashguard
- · Interlock channel
- · VITO oil filtration
- · VITO oil tester

Certifications

· CB, UL, CE, UKCA

Technical drawings (mm)





